



## TECHNICAL DATA SHEET

# MOTOCYCLE OIL 4T 15W-40 JASO MA

### PRODUCT DESCRIPTION AND USE

EN: NP MOTOCYCLE OIL 4T 15W/40 is the motorcycle oil developed for four stroke engines showing high performance under all road and driving conditions. Specially formulated to meet needs of world's leading motorcycle manufacturers and to provide excellent protection under any operation condition. NP MOTOCYCLE OIL 4T 15W/40 is recommended for four seasons for four stroke motorcycles whose viscosity and performance level requirements are suitable.

### FEATURES AND BENEFITS

- ✓ Provides high performance under all climate conditions and even under the heaviest operation conditions.
- ✓ Prevents rupture of oil film by providing better film resistance thanks to its high viscosity index.
- ✓ Provides maximum protection against abrasion which may occur during the first operation thanks to its easy fluidity capacity even at very low temperatures.
- ✓ Maintains its performance during oil change period recommended by vehicle manufacturers thanks to its outstanding thermal and oxidation stability.
- ✓ Keeps the engine clean by keeping formation of deposit and mud under control which appear at high temperatures thanks to the improved active cleaning capability.

### MEETS THE SPECIFICATION AND APPROVALS

API SL, JASO MA

### TYPICAL PROPERTIES

TEST	UNIT	METOD	TYPICAL VALUES
Density ,@ 15 °C	g/cm <sup>3</sup>	ASTM 4052	0,88
K. Viscosity,@ 100 °C	cSt	ASTM D 445	12,5-16,3
Viscosity Index		ASTM D 2270	125
Flash Point	°C	ASTM D 92	230
Pour Point	°C	ASTM D 97	-25

\*The above values may vary slightly according to production.

### HEALTH, SAFETY AND ENVIRONMENTAL RECOMMENDATIONS

Should not make contact with the skin, should not be swallowed and vapors should not be inhaled. In case of contact with the skin or eyes, wash with plenty of water and seek medical attention if necessary. When swallowed, victim should not be vomiting and immediate medical attention should be sought. When the vapors are inhaled, breathe heavily in fresh air and, if necessary, seek medical attention. Used oils should not be disposed to garbage, sewage and should be collected by licensed waste oil collectors. It should not be mixed with any petroleum products or chemicals. It should not be burned in furnaces and boilers. Should be kept away from children. Empty containers should not be thrown to the garbage or left in the environment and should be delivered to licensed recycling companies.

For more information, please refer to the 'Material Safety Data Sheet'

### STORAGE CONDITIONS

Packaging should not be exposed to extended periods of direct sunlight. Packaging should not be in contact with water. Oils should not come into contact with dust and should be kept away from dusty environments. Ambient temperature should not exceed 40 ° C. The user is solely responsible for using the product according to its purpose and for complying with the laws and regulations in effect. Nil Petrol San. Ve Tic. A.Ş. may not be held responsible for damages and loss due to the use of the product outside its normal or intended uses or due to inherent dangers of the product and its consequences.

### TYPES OF PACKING

900 ML, 1L, 200L, 1000L