



PRO WF6000

PRODUCT DESCRIPTION AND USE

NP PRO WF6000 is a pure sulfur, nitrogen-free, high purity USP grade white mineral oil formulated from highly refined, low processed, low pour point base oils that meets the extreme purity requirements of the United States Pharmacopoeia. It is used in an infinite number of applications including medical formulations, ointments, laxatives, depot vaccines, hair oils, hair creams, cosmetics, facial creams and lotions, gelatin capsules, protective coatings for fruits and vegetables, veterinary preparations, egg preservatives etc.

TYPICAL PROPERTIES

TEST	UNIT	METHOD	TYPICAL VALUES
Density, @ 25 °C	g/cm ³	ASTM D 4052	0,845-0,900
K. Viscosity, @ 40 °C	cSt	ASTM D 445	61,2-74,8
Flash Point	°C	ASTM D 92	200
Pour Point	°C	ASTM D 97	-9
Color	Saybolt	ASTM D 156	+30

The above values may vary slightly according to production.

HEALTH, SAFETY AND ENVIRONMENTAL RECOMMENDATIONS

Should not make contact with the skin, should not be swallowed and vapors should not be inhaled. In case of contact with the skin or eyes, wash with plenty of water and seek medical attention if necessary. When swallowed, victim should not be vomiting and immediate medical attention should be sought. When the vapors are inhaled, breathe heavily in fresh air and, if necessary, seek medical attention. Used oils should not be disposed to garbage, sewage and should be collected by licensed waste oil collectors. It should not be mixed with any petroleum products or chemicals. It should not be burned in furnaces and boilers. Should be kept away from children. Empty containers should not be thrown to the garbage or left in the environment and should be delivered to licensed recycling companies.

For more information, please refer to the 'Material Safety Data Sheet'

STORAGE CONDITIONS

Packaging should not be exposed to extended periods of direct sunlight. Packaging should not be in contact with water. Oils should not come into contact with dust and should be kept away from dusty environments. Ambient temperature should not exceed 40 °C. The user is solely responsible for using the product according to its purpose and for complying with the laws and regulations in effect. Nil Petrol San. Ve Tic. A.Ş. may not be held responsible for damages and loss due to the use of the product outside its normal or intended uses or due to inherent dangers of the product and its consequences.

TYPES OF PACKING

200 L, 1000L