



## TECHNICAL DATA SHEET

# RUBBER GREASE NO : 2-3

### PRODUCT DESCRIPTION AND USE

NP RUBBER GREASE, is general purpose green grease formulated with high quality base oils, calcium soap and cohesion enhancing components. It is suitable for medium and high speed bearings, low speed flat bearings and chassis applications with operating temperatures not exceeding 70 °C.

### FEATURES AND BENEFITS

- ✓ Adheres well to metal in moist or aqueous environments and shows excellent resistance to washing with water.
- ✓ Resists abrasion and corrosion.
- ✓ Provides effective lubrication on metal surfaces thanks to its fibrous structure.

### TYPICAL PROPERTIES

TYPE OF SOAP	METOD	CA	CA	CA	CA
COLOR	-	GREEN	GREEN	GREEN	GREEN
NLGI	-	0	1	2	3
DROP POINT, °C, MIN	ASTM D 566	90	90	95	95
PROCESSED PENETRATION 25 oC	ASTM D 217	355-385	310-340	265-295	220-250
WORKING TEMPERATURE, oC	-	60	70	70	70

\*The above values may vary slightly according to production.

### HEALTH, SAFETY AND ENVIRONMENTAL RECOMMENDATIONS

Should not make contact with the skin, should not be swallowed and vapors should not be inhaled. In case of contact with the skin or eyes, wash with plenty of water and seek medical attention if necessary. When swallowed, victim should not be vomiting and immediate medical attention should be sought. When the vapors are inhaled, breathe heavily in fresh air and, if necessary, seek medical attention. Used oils should not be disposed to garbage, sewage and should be collected by licensed waste oil collectors. It should not be mixed with any petroleum products or chemicals. It should not be burned in furnaces and boilers. Should be kept away from children. Empty containers should not be thrown to the garbage or left in the environment and should be delivered to licensed recycling companies.

For more information, please refer to the 'Material Safety Data Sheet'

### STORAGE CONDITIONS

Packaging should not be exposed to extended periods of direct sunlight. Packaging should not be in contact with water. Oils should not come into contact with dust and should be kept away from dusty environments. Ambient temperature should not exceed 40 ° C. The user is solely responsible for using the product according to its purpose and for complying with the laws and regulations in effect. Nil Petrol San. Ve Tic. A.Ş. may not be held responsible for damages and loss due to the use of the product outside its normal or intended uses or due to inherent dangers of the product and its consequences.

### TYPES OF PACKING

900GR, 3.6KG, 14KG, 180KG