



TECHNICAL DATA SHEET

CLASSIC CX 4000 SAE 40

PRODUCT DESCRIPTION AND USE

NP CLASSIC CX 4000 SAE 40, high viscosity indexed single grade engine oil manufactured by adding package additives special to paraffinic based base oils. Used for oil pans of diesel engines operated under soft and medium level conditions.

FEATURES AND BENEFITS

- ✓ Keeps the engine clean by preventing formation of residues and deposits.
- ✓ Protects the engine being under heavy duty against oxidation and abrasion thanks to its high film resistance.
- ✓ Prevents rust and corrosion on metal surfaces thanks to additives in its composition.
- ✓ Resists against piston varnishing by minimizing combustion chamber deposits.
- ✓ Prevents performance loss by keeping the engine clean.
- ✓ Maintains its fluidity at low temperatures and doesn't foam.

MEETS THE SPECIFICATION AND APPROVALS

API CD/SF

TYPICAL PROPERTIES

TEST	UNIT	METOD	TYPICAL VALUES
Density ,@ 15 °C	g/cm ³	ASTM 4052	0,88
K. Viscosity,@ 100 °C	cSt	ASTM D 445	14,3
Viscosity Index		ASTM D 2270	94
Flash Point	°C	ASTM D 92	230
Pour Point	°C	ASTM D 97	-15

*The above values may vary slightly according to production.

HEALTH, SAFETY AND ENVIRONMENTAL RECOMMENDATIONS

Should not make contact with the skin, should not be swallowed and vapors should not be inhaled. In case of contact with the skin or eyes, wash with plenty of water and seek medical attention if necessary. When swallowed, victim should not be vomiting and immediate medical attention should be sought. When the vapors are inhaled, breathe heavily in fresh air and, if necessary, seek medical attention. Used oils should not be disposed to garbage, sewage and should be collected by licensed waste oil collectors. It should not be mixed with any petroleum products or chemicals. It should not be burned in furnaces and boilers. Should be kept away from children. Empty containers should not be thrown to the garbage or left in the environment and should be delivered to licensed recycling companies.

For more information, please refer to the 'Material Safety Data Sheet'

STORAGE CONDITIONS

Packaging should not be exposed to extended periods of direct sunlight. Packaging should not be in contact with water. Oils should not come into contact with dust and should be kept away from dusty environments. Ambient temperature should not exceed 40 °C. The user is solely responsible for using the product according to its purpose and for complying with the laws and regulations in effect. Nil Petrol San. Ve Tic A.Ş. may not be held responsible for damages and loss due to the use of the product outside its normal or intended uses or due to inherent dangers of the product and its consequences.

TYPES OF PACKING

1L, 4L, 5 L, 16 L, 200 L, 1000L