



## CLASSIC CX 4000 HD 40

### PRODUCT DESCRIPTION AND USE

NP CLASSIC CX 4000 HD 40, high viscosity indexed single grade superior quality oil formulated by adding detergent-disperser type package additive into high quality base oils. Used for high speed and high power diesel engines of construction equipment and heavy vehicles.

### FEATURES AND BENEFITS

- ✓ Minimizes deposit formation under heavy operation conditions and prevents abrasion.
- ✓ Maintains its fluidity at low temperatures since it is high viscosity indexed.
- ✓ Protects the surface against chemical effects of acidic residues by forming an oil film on metal surfaces.
- ✓ Prevents the humidity and water leaking into the engine to cause rusting.
- ✓ Keeps the engine clean and increases its combustion efficiency.
- ✓ Minimizes abrasion at high temperatures and under heavy weight.
- ✓ Neutralizes acidic materials which may form from the sulfur within fuel thanks to its adequate TBN value. Helps to extend oil change periods and saves operating costs.

### MEETS THE SPECIFICATION AND APPROVALS

API CF/SJ

### TYPICAL PROPERTIES

TEST	UNIT	METOD	TYPICAL VALUES
Density ,@ 15 °C	g/cm <sup>3</sup>	ASTM 4052	0,88
K. Viscosity,@ 100 °C	cSt	ASTM D 445	14,3
Viscosity Index		ASTM D 2270	94
Flash Point	°C	ASTM D 92	230
Pour Point	°C	ASTM D 97	-15

\*The above values may vary slightly according to production.

### HEALTH, SAFETY AND ENVIRONMENTAL RECOMMENDATIONS

Should not make contact with the skin, should not be swallowed and vapors should not be inhaled. In case of contact with the skin or eyes, wash with plenty of water and seek medical attention if necessary. When swallowed, victim should not be vomiting and immediate medical attention should be sought. When the vapors are inhaled, breathe heavily in fresh air and, if necessary, seek medical attention. Used oils should not be disposed to garbage, sewage and should be collected by licensed waste oil collectors. It should not be mixed with any petroleum products or chemicals. It should not be burned in furnaces and boilers. Should be kept away from children. Empty containers should not be thrown to the garbage or left in the environment and should be delivered to licensed recycling companies.

For more information, please refer to the 'Material Safety Data Sheet'

### STORAGE CONDITIONS

Packaging should not be exposed to extended periods of direct sunlight. Packaging should not be in contact with water. Oils should not come into contact with dust and should be kept away from dusty environments. Ambient temperature should not exceed 40 °C. The user is solely responsible for using the product according to its purpose and for complying with the laws and regulations in effect. Nil Petrol San.ve Tic A.Ş. may not be held responsible for damages and loss due to the use of the product outside its normal or intended uses or due to inherent dangers of the product and its consequences.

### TYPES OF PACKING

1L, 4L, 5L, 16L, 20L, 200L, 1000L